

LINTEL SCHEDULE

CODE	LINTEL SIZE
L-1	2-3 1/2" x 3 1/2" STL LINTEL JL
L-2	3-2x10
L-3	4-2x10

FLOOR-ON-GROUND INTERIOR
CONCRETE STRENGTHS
MPa @ 5% TO 8% AIR ENTRY
MPa @ 5% TO 8% AIR ENTRY
MPa @ 5% TO 8% AIR ENTRY
MPa @ 5% TO 8% AIR ENTRY

9.30.1.2(1) REQUIRES WATER RESISTANCE FINISHED FLOORING IN BATHROOMS, KITCHENS, LAUNDRY, PUBLIC ENTRANCE HALLS AND GENERAL STORAGE AREAS.

TRUSSES ARE TO BE ERECTED & BRACED ACCORDING TO ENGINEERED PLANS.

EXTERIOR SLAB
CONCRETE STRENGTHS
MPa @ 5% TO 8% AIR ENTRY
MPa @ 5% TO 8% AIR ENTRY
MPa @ 5% TO 8% AIR ENTRY
MPa @ 5% TO 8% AIR ENTRY

FOR PERMIT & TENDER	02/02/10
ISSUED:	DATE:

THIS DRAWING IS COMPLEMENTARY & MUST BE READ IN CONJUNCTION WITH ALL THE OTHER DRAWINGS AND/OR SPECIFICATIONS. REPORT ANY INCONSISTENCIES TO THE ARCHITECT.

PROJECT:
NEW SUMMER CAMP PROPERTY
THE CHURCH OF JESUS CHRIST OF LATTER-DAY SAINTS

DRAWING TITLE:
FLOOR PLAN & SECTIONS

SCALE: A5 NOTED	DRAWING NUMBER:
DRAWN BY: DWG	A4 OF 6
CHECKED BY: GW	28034A4-1

